



PN-G3005N-E30F

Gun camera



- HD Night Vision: 3MP, clear visibility day and night, ensuring 24/7 surveillance.
- Remote Control: Easily monitor live activity anytime, anywhere via phone or computer.
- Smart Two-Way Audio: Real-time communication for quicker resolution of unexpected issues.
- Precise Alarm: Immediate alerts for abnormal behavior, ensuring prompt response.
- True Color Restoration: Auto white balance for natural colors and more vivid images.
- Efficient Video Compression: Dual H.264/H.265 compression for optimized image quality and bandwidth.



Parameter	Value
Model	PN-G3005N-E30F
Image Sensor	1/3" 3MP CMOS (or equivalent functional parts)
Fixed Lens	4mm, 6mm, 8mm (lens options available)
Signal-to-Noise Ratio	≥50dB
Minimum Illumination	Color mode: 0.01Lux; Black and white mode: 0.001Lux
Color/Black Switch	Auto, manual, scheduled control
Wide Dynamic Range	Supported
White Balance	Automatic
3D Noise Reduction	Supported
Video Compression Standard	H.264/H.265
Image Resolution	Main stream: 25FPS@(2304×1296, 1920×1080, 1280×720); Sub-stream: D1, VGA, 640×360
Output Stream	Supports adjustable bitrate from 0.1Mbps to 3Mbps, adjustable frame rate from 1 to 25 FPS
Audio	G.711 encoding standard, supports two-way audio intercom, supports audio-video synchronization (optional)
Motion Detection	Supported
Anti-Face Overexposure	Supported
De-fog Function	Supported
Network Interface	1 RJ45 10/100M self-adaptive Ethernet port
Protocols	Supports HTTP/RTSP/DHCP/NTP/ONVIF and other network protocols
Power Supply	DC12V / POE
Power Consumption	6W Max
Operating Temperature	-10°C ~ 50°C
Operating Humidity	0% ~ 90% RH (non-condensing)
Device Dimensions (mm)	180*85*90
Protection level	IP66

* The Company reserves the right of final interpretation of the information in the documents and is subject to change without prior notice.