


PN-G3005N-H30F

Gun camera



- Clear Image Quality: 3MP resolution, clear night vision for both day and night.
- Two-way Audio: Real-time voice intercom for immediate on-site communication.
- Remote Monitoring: Access anytime, anywhere, with easy viewing on mobile or PC.
- Smart Alarm: Instant alerts triggered by abnormal behavior, ensuring safety.
- High-Definition Sensor: 1/3" CMOS sensor, offering true-to-life, natural color reproduction.
- Flexible Bitrate: Supports dynamic bitrate adjustment, optimizing bandwidth and clarity.



Parameter	Value
Model	PN-G3005N-H30F
Image Sensor	1/3" 3MP CMOS (or equivalent functional specification part)
Fixed Lens	4mm, 6mm, 8mm (Lens options available)
Signal-to-Noise Ratio	≥50dB
Minimum Illumination	Color mode: 0.01Lux Black & White mode: 0.001Lux
Color/Black Switch	Auto, Manual, Timed Control
Wide Dynamic Range	Supported
White Balance	Auto
3D Noise Reduction	Supported
Video Compression Standard	H.264/H.265
Image Resolution	Main stream: 25FPS @(2304×1296, 1920×1080, 1280×720) Sub stream: D1, VGA, 640×360
Output Stream	Supports stream 0.1Mbps-3Mbps adjustable, supports frame rate 1~25fps adjustable
Audio	G.711 encoding standard, supports bidirectional intercom, supports audio-video synchronization (optional)
Motion Detection	Supported
Anti-Face Overexposure	Supported
De-fog Function	Supported
Network Interface	1 RJ45 10/100M self-adaptive Ethernet interface
Protocols	Supports HTTP/RTSP/DHCP/NTP/ONVIF and other network protocols
Power Supply	DC12V / POE
Power Consumption	6W Max
Operating Temperature	-10°C ~ 50°C
Operating Humidity	0% ~ 90% RH (non-condensing)
Device Dimensions (mm)	180*85*90
Protection level	IP66

* The Company reserves the right of final interpretation of the information in the documents and is subject to change without prior notice.