



PN-G4005L-P40Z

Gun camera



- HD Night Vision: 4MP resolution, providing clear and detailed images day and night.
- Two-Way Audio: Optional feature, enabling real-time remote communication with the site.
- Remote Monitoring Anytime: Real-time viewing via phone or computer, keeping you in control of the scene.
- Intelligent Alarm System: Alerts triggered by abnormal events, ensuring a timely response to emergencies.
- Precise Color Reproduction: Automatic white balance for natural, realistic colors and fine details.
- Flexible Bitrate Adjustment: Supports 0.1M~4Mbps adjustment, balancing image quality and bandwidth.



Parameter	Value
Model	PN-G4005L-P40Z
Image Sensor	1/1.8" 4MP CMOS (or equivalent functional specifications)
Lens	Motorized zoom 3.6~11mm
Signal-to-Noise Ratio	≥50dB
Minimum Illumination	Color mode: 0.01Lux, Black and white mode: 0.001Lux
Color/Black Switch	Night full-color
Wide Dynamic Range	Supported
White Balance	Automatic
3D Noise Reduction	Supported
Video Compression Standard	H.264/H.265
Image Resolution	Main stream: 25FPS @(2880×1620, 2688×1520, 2560×1440, 2304×1296, 1920×1080, 1280×720) Sub-stream: D1, VGA, 640×360
Output Bitrate	Adjustable bitrate from 0.1Mbps to 4Mbps, frame rate adjustable from 1~25fps
Audio	G.711 codec, supports two-way audio, supports audio and video synchronization (optional)
Motion Detection	Supported
Anti-Facial Overexposure	Supported
De-fog Function	Supported
Network Interface	1 RJ45 10/100M adaptive Ethernet interface
Protocols	Supports HTTP/RTSP/DHCP/NTP/ONVIF and other network protocols
Power Supply	DC12V / POE
Power Consumption	6W Max
Operating Temperature	-10°C ~ 50°C
Operating Humidity	0%~90% RH (non-condensing)
Device Dimensions (mm)	200*85*90
Protection level	IP66

* The Company reserves the right of final interpretation of the information in the documents and is subject to change without prior notice.